

HIGHLIGHTS

- Excellent gloss
- Low Maintenance
- Good Durability



People's

TYPICAL PROPERTIES

- Specific Gravity: **1.02**
- Solid Content: **Hi-Shine (25%)**
- pH: **8.3**
- Leveling: **Excellent**
- Film Formation: **Excellent**
- Gloss: **Excellent**
- Water resistance: **Excellent**
- Detergent resistance: **Very Good - Excellent**
- Removability: **Excellent**
- Black heel mark resistance: **Very Good**
- Slip Resistance: **0.6** (James Static Coefficient of Friction)
- Odor: **Slight Ammonia**
- Appearance: **White Emulsion**

SAFETY CAUTIONS

- Keep out of reach of children.
- It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation.
- Refer to M.S.D.S. for additional safety information.

HMIS RATINGS



Hi-Shine 25% Acrylic Polymer Floor Finish

This high solids, metal-crosslinked, modified acrylic floor finish provides excellent lay down gloss and low maintenance. It can be maintained with either conventional low-speed programs or infrequent, (2-3 times a week) high speed burnishing.

USE DIRECTIONS (New or existing floors)

- 1) Thoroughly strip floor with a stripper.
- 2) Rinse floor thoroughly with clean water.
- 3) Apply a sealer base (optional) to worn floors or high traffic floors to improve wear-resistance and enhance gloss.
- 4) Apply 2-4 coats of floor finish in uniform thin coats allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather.

MAINTENANCE

- 1) Sweep as necessary.
- 2) Damp mop or scrub lightly with a mild, neutral detergent.
- 3) Spray buff or buff lightly with appropriate pad. Also excellent for high-speed buffing.
- 4) In high traffic areas, recoat worn spots as necessary.



Distributed by

People's Janitorial Supply

P. O. Box 68

Forest Park, GA 30298

Phone: 404-363-2226

Fax: 404-363-3380

86555TEC-H6453-1203