



THE PEOPLES CHOICE

Wet Look 18% Floor Finish

HIGHLIGHTS

Excellent gloss
Superior response to high speed burnishing
Good Durability

TYPICAL PROPERTIES

Specific Gravity: 1.02
Solid Content: 18%
pH: 8.3
Leveling: Excellent
Film Formation: Excellent
Gloss: Excellent
Water resistance: Excellent
Detergent resistance: Very Good - Excellent
Removability: Excellent
Black heel mark resistance: Very Good
Slip Resistance: 0.6 (James Static Coefficient of Friction)
Odor: Slight Ammonia
Appearance: White Emulsion

SAFETY CAUTIONS

Keep out of reach of children.

It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation.

Refer to SDS for additional safety information.

This metal-crosslinked, modified acrylic floor finish provides excellent lay down gloss and superior response to high speed burnishing. It can be maintained with either conventional low-speed programs or infrequent (2-3 times a week) high speed burnishing.

USE DIRECTIONS (New or existing floors)

- 1) Thoroughly strip floor with a stripper.
- 2) Rinse floor thoroughly with clean water.
- 3) Apply a sealer base (optional) to worn or high traffic floors to improve wear resistance and enhance gloss.
- 4) Apply 2-4 coats of floor finish in uniform thin coats allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather.

MAINTENANCE

- 1) Sweep as necessary.
- 2) Damp mop or scrub lightly with a mild, neutral detergent.
- 3) Spray buff or buff lightly with appropriate pad. Also excellent for high-speed buffing.
- 4) In high traffic areas, recoat worn spots as necessary.



P.O. Box 68 • Forest Park, GA 30298
404-363-2226 Phone • 404-363-3380 Fax