



# Red Hot SS

## High Performance Floor Stripper



A fast acting formula with powerful active ingredients that give excellent results after lengthy periods between stripping operations.

### DIRECTIONS:

Read all directions and Safety Data Sheets (SDS) before using.

1. Mix stripper with cold water per the following dilutions:  
Heavy coating removal: 1:4 (32 US oz per gallon / 250 ml per 1 liter of water).  
Normal coating removal: 1:6 (21.5 US oz per gallon / 166 ml per 1 liter of water).  
Light coating removal: 1:8 (16 US oz per gallon / 125 ml per 1 liter of water).
2. Apply solution liberally to the floor and allow to soak for 10 minutes ensuring the solution does not dry.
3. Scrub floor with automatic scrubber or stripping machine. Pick up dirty solution with automatic scrubber or wet vac.
4. Rinse thoroughly with clean water and allow floor to dry completely before applying any finish.

### Product Info:

<b>Product Code</b>	567GL5PEO
<b>Volume</b>	2.5 US gallons (9,5 liters)
<b>Shipping Package</b>	2 x 2.5 gallons (2 x 9,5 liters)
<b>Pallet Quantity</b>	48

### Surfaces:

Vinyl composition tile ("VCT"), most types of terrazzo, marble and quarry tile. Not recommended to be used in contact with wood, rubber, painted surfaces or on asphalt or asbestos tile.  
NOTE: Test floor for color fastness in an inconspicuous area.

### Technical Data:

<b>Description</b>	Fast acting floor stripper
<b>Appearance</b>	Red liquid
	11.5 (as supplied)
<b>pH</b>	11.2 (1:4)
ASTM E70-07 (2015)	11.0 (1:6)
	10.8 (1:8)
<b>Viscosity (Brookfield)</b>	<10 centipoise
@ 68°F/20°C	54.5% (as supplied)
<b>VOC</b>	10.5% (1:4)
40 CFR Part 59 Subpart C	7.4% (1:6)
	5.8% (1:8)
<b>Fragrance</b>	Floral fragrance
<b>Shelf Life</b>	2 years
ASTM D1791-93 (2015)	
<b>Density</b>	8.0 lb/gal @ 68°F
ASTM D1475-13 (2015)	0.96 kg/L @ 20°C
<b>Flash Point</b>	>200°F (> 93°C)
ASTM D56-05 (2010)	
<b>Container</b>	2.5 US gallons



Peoples Janitorial Supplies  
955 Main St  
Forest Park, GA 30297  
404-363-2226  
peoplesupplies.com