



# Resurrection

## Cleaner/Enhancer



An effective one step cleaner and enhancer. May be applied by automatic scrubber or damp-mop. Cleans and enhances coating for a brilliant wet-look shine when burnished with UHS burnishers.

### DIRECTIONS:

Read all directions and Safety Data Sheets (SDS) before using.

1. Sweep the floor with a dust mop.
2. Dilute product at:  
1:32 (32 ml per 1 liter or 4 US oz per gallon of water)  
for automatic scrubber application or  
1:64 (16 ml per 1 liter or 2 US oz per gallon of water)  
for mop-on application.
3. Dispense in automatic scrubber or mop bucket.
4. Scrub the floor and pick up solution in one pass or scrub with a damp mop.
5. Allow floor to dry thoroughly.
6. Burnish floor.

### Product Info:

<b>Product Code</b>	259GL4PEO
<b>Volume</b>	1 US gallon (3,8 liters)
<b>Shipping Package</b>	4 x 1 gallon (4 x 3,8 liters)
<b>Pallet Quantity</b>	48

### Surfaces:

Vinyl composition tile ("VCT") and most types of terrazzo, marble, concrete and quarry tile and treated wood floors.

### Technical Data:

<b>Description</b>	Water-based cleaner/enhancer
<b>Appearance</b>	Clear green liquid
<b>pH</b> <small>ASTM E70-07 (2015)</small>	9.0 (as supplied)
<b>Viscosity (Brookfield)</b> <small>@ 68°F/20°C</small>	<10 centipoise
<b>Dry Time</b>	about 15 minutes
<b>VOC</b> <small>40 CFR Part 59 Subpart D</small>	0.01% (as supplied) <0.01% (1:32, 1:64 dilution)
<b>Non-volatile solids</b> <small>ASTM D2834-95 (2015)</small>	11%
<b>Fragrance</b>	Lemon-lime
<b>Shelf Life</b> <small>ASTM D1791-93 (2015)</small>	1 year
<b>Density</b> <small>ASTM D1475-13 (2015)</small>	8.4 lb/gal @ 68°F 1.01 kg/L @ 20°C
<b>Freeze/Thaw</b> <small>ASTM D3209-93 (2015)</small>	Passes 3 cycles
<b>Container</b>	1 US Gallon



Peoples Janitorial Supplies  
955 Main St  
Forest Park, GA 30297  
404-363-2226  
peoplesupplies.com