

HIGHLIGHTS

- Outstanding durability and gloss retention with low maintenance programs
- Modified acrylic polymers
- Unsurpassed leveling
- Outstanding gloss
- Reduced sensitivity to ambient application conditions
- Excellent burnish response with no powdering or dusting
- High durability
- Decreased labor cost through less frequent need to buff, burnish and recoat, and a reduction in the number of floor strippings

TYPICAL PROPERTIES

• Specific Gravity: 1.04

• Solids: 25%

• pH: 8.5

James Static Coefficient of Friction: 0.6

Leveling: Excellent

• Film Formation: Excellent

Gloss: Excellent

• Water resistance: Excellent

• Detergent resistance: Excellent

• Removability: Excellent

• Black heal mark resistance: Excellent

• Odor: Mild acrylic

• Appearance: White emulsion

SAFETY CAUTIONS

Keep out of reach of children. It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation.

Refer to SDS for additional safety information.

Hi-Shine 25% Acrylic Polymer Floor Finish

This high solids, metal-crosslinked, modified acrylic floor finish provides excellent lay down gloss and superior response to high speed burnishing. It can be maintained with either conventional low-speed programs or infrequent (2-3 times a week) high speed burnishing.

USE DIRECTIONS (New or existing floors)

- 1) Thoroughly strip floor with a stripper.
- 2) Rinse floor thoroughly with clean water.
- Apply a sealer base (optional) to worn floors or high traffic floors to improve wear-resistance and enhance gloss.
- 4) Apply 2-4 coats of floor finish in uniform thin coats allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather.

MAINTENANCE

- 1) Sweep as necessary.
- 2) Damp mop or scrub lightly with a mild, neutral detergent.
- 3) Spray buff or buff lightly with appropriate pad. Also excellent for high-speed buffing.
- 4) In high traffic areas, recoat worn spots as necessary.

